

## Thin Walled Microducts, 12/10 mm

Thin walled microducts are normally installed in existing pipes with limited space and where thick walled ducts will not fit.

The ducts have an outer/inner diameter of 12/10 mm and are suitable for installation of micro cables and nano cables. The ducts are made of HDPE with and have a low friction inner surface for best blowing performance.

**DESIGN:** Thin walled ducts  
**TYPE:** Installation in existing pipes  
**CAPACITY:** single ducts  
**DIMENSIONS:** OD/ID Ø12/10 mm  
**LENGTHS:** 2100 m

Microducts, 12/10mm		Diameter	Weight	Length
Product No.	Product Name	OD/ID ø (mm)	kg/km	m
MPB30262/OG1	Microduct 12/10 mm, Orange	12/10	42	2100
MPB30262/YE1	Microduct 12/10 mm, Yellow	12/10	42	2100
MPB30262/RD1	Microduct 12/10 mm, Red	12/10	42	2100
MPB30262/WH1	Microduct 12/10 mm, White	12/10	42	2100
MPB30262/GN1	Microduct 12/10 mm, Green	12/10	42	2100
MPB30262/VT1	Microduct 12/10 mm, Violet	12/10	42	2100
MPB30262/BU1	Microduct 12/10 mm, Blue	12/10	42	2100
MPB30262/GY1	Microduct 12/10 mm, Grey	12/10	42	2100
MPB30262/TQ1	Microduct 12/10 mm, Turquoise	12/10	42	2100
MPB30262/BK1	Microduct 12/10 mm, Black	12/10	42	2100
MPB30262/BN1	Microduct 12/10 mm, Brown	12/10	42	2100
MPB30262/PK1	Microduct 12/10 mm, Pink	12/10	42	2100

