

## Patch panels

# FIBER-PATCH K

19" 3/1U aluminium termination box  
Up to 144 fibers

4\_1\_23

### Composed of

- 19" 3/1U rack with 1U tray for extra loose tubes or extra cables
- For 12 x 7 TE or 10 x 8 TE plug-in modules 3U
- 3U 7 TE or 8 TE cover plate for empty slots
- Optional: angle for backward adjustment (70 mm)

### Description

- Empty rack
- Cable fastening plate at the rear
- Cable handling set
- Fixing materials

### Application

- Indoors
- Junction or distribution box



### Technical data

Type	Module 7TE (max.)	Module 8TE (max.)	Module attachment	Dimensions (l x h x d)	Weight kg	Material/Colour box/front
3/1 U	12	10	screwed	483 x 177 x 274	3.4	Alu / Alu

## Patch panels

# Fiber module, 7 HP for FIBER-PATCH K

Splice version for 19" U racks with card guide

4\_1\_30\_1

### Composed of

- Module attachment: screwed
- Dimensions: 35.2 x 133 x 232 mm
- Weight: 1.2 kg

### Description

- Anodised aluminium front panel with numbered slots
- Powder coated steel base plate
- Pre-assembled
- Optional connectors and number of splices available

### Application

- Indoors



### With connector singlemode APC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 7TE	LC-D	6	3	24
3HE 7TE	LSH	12	3	24
3HE 7TE	SC	12	3	24

### With connector singlemode PC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 7TE	LC-D	6	3	24
3HE 7TE	LSH	12	3	24
3HE 7TE	SC	12	3	24

### With connector multimode PC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 7TE	LC-D	6	3	24
3HE 7TE	LSH	12	3	24
3HE 7TE	LSH-D	6	3	24
3HE 7TE	SC	12	3	24

LSH is equivalent to E-2000, which is a registered Tradename of the company DIAMOND SA.

## Patch panels

# Fiber module, 8 HP for FIBER-PATCH K

Splice version for 19" U racks with card guide

4\_1\_30\_2

### Composed of

- Module attachment: screwed
- Dimensions: 40.6 x 133 x 232 mm
- Weight: 1.3 kg

### Description

- Anodised aluminium front panel with numbered slots
- Powder coated steel base plate
- Pre-assembled
- Optional connectors and number of splices available

### Application

- Indoors



### With connector singlemode APC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 8TE	LC-D	6	3	24
3HE 8TE	LSH	12	3	24
3HE 8TE	SC	12	3	24

### With connector singlemode PC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 8TE	LC-D	6	3	24
3HE 8TE	LSH	12	3	24
3HE 8TE	SC	12	3	24

### With connector multimode PC

Type	Connector type	Connector (max.)	Tray (max.)	Splices (max.)
3HE 8TE	LC-D	6	3	24
3HE 8TE	LSH	12	3	24
3HE 8TE	LSH-D	6	3	24
3HE 8TE	SC	12	3	24
3HE 8TE	SC-D	6	3	24
3HE 8TE	BFOC	12	2	12
3HE 8TE	FC	12	2	12

LSH is equivalent to E-2000, which is a registered Tradename of the company DIAMOND SA.  
BFOC is equivalent to ST, which is a registered Tradename from the company LUCENT Technologies.